NSN 5305-00-402-0126

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-402-0126 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.184 inches and 0.196 inches **Fastener Length:** Between 0.600 inches and 0.640 inches **Head Style:** Fillister **Head Diameter:** Between 0.166 inches and 0.183 inches **Head Height:** Between 0.069 inches and 0.079 inches **First Diameter From Head:** Between 0.073 inches and 0.078 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.404 inches and 0.456 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-00-402-0126

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0