## NSN 5305-00-402-2606

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-402-2606 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.276 inches and 0.317 inches **Fastener Length:** Between 0.719 inches and 0.750 inches **Head Style:** Pan **Head Diameter:** Between 0.306 inches and 0.322 inches **Head Height:** Between 0.105 inches and 0.115 inches **First Diameter From Head:** Between 0.120 inches and 0.130 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.433 inches and 0.443 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 60000 pounds per square inch **Externally Relieved Body Diameter Quantity:** Material: Steel **Material Specification:** Qq-s-633 federal specification single material response **Surface Treatment:** Cadmium or chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification all treatment responses **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

--

## NSN 5305-00-402-2606

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0