NSN 5305-00-402-4544

Mil-std (military Standard):

Mil-s-5002 spec.

Externally Relieved Body Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-402-4544 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.340 inches and 0.400 inches **Fastener Length:** 2.000 inches **Head Style:** Flat chamfer First Diameter From Head: 0.090 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.600 inches and 1.660 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 302 or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 309 or steel comp 310 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 **Material Specification:** Aisi a582 assn standard all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Mil-s-5002 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig: A003b0