## NSN 5305-00-402-4736

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-402-4736

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.450 inches and 0.510 inches
Fastener Length:
Between 4.230 inches and 4.250 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.590 inches and 0.650 inches
Head Height:
Between 0.110 inches and 0.130 inches
Shoulder Diameter:
0.410 inches first shoulder and 0.470 inches first shoulder
Shoulder Length:
0.730 inches first shoulder and 0.750 inches first shoulder
Internal Drive Style:
Slot
Thread Diameter:
0.250 inches
Thready Qty Per Inch (tpi):
20
Shoulder Shape:
Round first shoulder
Material:
Steel comp 303
Material Specification:
Mil-s-7720, comp 303s military specification single material response
Surface Treatment:
Passivate
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0

## NSN 5305-00-402-4736

Shoulder Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-7720 spec.