## NSN 5305-00-402-6246

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-402-6246



### 3a **Thread Direction: Right-hand Thread Length:** Between 0.512 inches and 0.553 inches Fastener Length: Between 0.594 inches and 0.625 inches **Head Style:** Oval countersunk **Head Diameter:** Between 0.285 inches and 0.332 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 62000 pounds per square inch

**Thread Class:** 

#### Countersink Angle:

Between 99.0 degrees and 101.0 degrees

#### Screw Material:

Aluminum alloy 2024

#### **Screw Material Specification:**

Qq-a-225/6 federal specification single material response

#### Head Surface Treatment:

Paint

Screw Surface Treatment:

Chromate

#### Head Surface Treatment Specification:

595, no. 27778 federal standard single treatment response

#### Screw Surface Treatment Specification:

Mil-c-5541 military specification single treatment response

Color:

Cream

**Thread Series Designator:** 

Unc

Shelf Life:

N/a

#### Unit Of Measure:

--

# NSN 5305-00-402-6246

Machine Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-c-5541 spec.

