

View Online at <https://aerobasegroup.com/nsn/5305-00-402-7879>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.089 inches and 0.094 inches

Fastener Length:

Between 0.370 inches and 0.380 inches

Head Style:

Pan no. 2

Head Diameter:

Between 0.205 inches and 0.219 inches

Head Height:

Between 0.058 inches and 0.068 inches

Washer Quantity:

1

Internal Drive Style:

Slot

Thread Diameter:

0.112 inches

Thready Qty Per Inch (tpi):

40

Min. Tensile Strength (psi):

55000 pounds per square inch

Hardness Rating:

40.0 rockwell c and 50.0 rockwell c

Primary Washer Outside Diameter:

Between 0.245 inches and 0.255 inches

Primary Washer Style:

Flat external teeth

Primary Washer Material Thickness:

Between 0.015 inches and 0.019 inches

Material:

Steel or steel comp 1050 or steel comp 1551 or steel comp 1552 or steel comp 1053 or steel comp 1055 or steel comp 1060

Material Specification:

Qq-s-633-canceled federal specification 1st material response or qq-w-409 federal specification 1st material response or qq-s-633 fs federal specification 2nd material response or qq-s-633 fs federal specification 3rd material response or qq-s-633 fs federal specification 4th material response or qq-s-633 fs federal specification 5th material response or qq-s-633 fs federal specification 6th material response or qq-s-633 fs federal specification 7th material response

Surface Treatment:

Nickel

Surface Treatment Specification:

Qq-n-290, class 6 type 2 federal specification single treatment response

Thread Series Designator:

UNc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0