

View Online at <https://aerobasegroup.com/nsn/5305-00-402-7879>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.089 inches and 0.094 inches

**Fastener Length:**

Between 0.370 inches and 0.380 inches

**Head Style:**

Pan no. 2

**Head Diameter:**

Between 0.205 inches and 0.219 inches

**Head Height:**

Between 0.058 inches and 0.068 inches

**Washer Quantity:**

1

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.112 inches

**Thready Qty Per Inch (tpi):**

40

**Min. Tensile Strength (psi):**

55000 pounds per square inch

**Hardness Rating:**

40.0 rockwell c and 50.0 rockwell c

**Primary Washer Outside Diameter:**

Between 0.245 inches and 0.255 inches

**Primary Washer Style:**

Flat external teeth

**Primary Washer Material Thickness:**

Between 0.015 inches and 0.019 inches

**Material:**

Steel or steel comp 1050 or steel comp 1551 or steel comp 1552 or steel comp 1053 or steel comp 1055 or steel comp 1060

**Material Specification:**

Qq-s-633-canceled federal specification 1st material response or qq-w-409 federal specification 1st material response or qq-s-633 fs federal specification 2nd material response or qq-s-633 fs federal specification 3rd material response or qq-s-633 fs federal specification 4th material response or qq-s-633 fs federal specification 5th material response or qq-s-633 fs federal specification 6th material response or qq-s-633 fs federal specification 7th material response

**Surface Treatment:**

Nickel

**Surface Treatment Specification:**

Qq-n-290, class 6 type 2 federal specification single treatment response

**Thread Series Designator:**

UNc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0