

View Online at <https://aerobasegroup.com/nsn/5305-00-402-8846>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.870 inches

**Fastener Length:**

1.750 inches

**Head Style:**

Pan

**Head Diameter:**

Between 0.306 inches and 0.322 inches

**Head Height:**

Between 0.105 inches and 0.115 inches

**First Diameter From Head:**

0.164 inches

**Second Diameter From Head:**

Between 0.119 inches and 0.124 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

0.180 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

0.880 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.164 inches

**Thready Qty Per Inch (tpi):**

32

**Externally Relieved Body Diameter Quantity:**

2

**Material:**

Steel comp 302 or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 309 or steel comp 310 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

C190000120, fsc-88818 mfr ref single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0