## NSN 5305-00-402-9110

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-402-9110 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.120 inches and 0.130 inches **Fastener Length:** 0.438 inches **Head Style:** Knurled no. 1 **Head Diameter:** Between 0.307 inches and 0.317 inches **Head Height:** Between 0.296 inches and 0.328 inches **First Diameter From Head:** Between 0.073 inches and 0.083 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.225 inches and 0.245 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Copper alloy 360 **Material Specification:** Qq-b-626, 1/2 h federal specification single material response **Surface Treatment:** Nickel **Surface Treatment Specification:** Qq-n-290 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

## NSN 5305-00-402-9110

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0