

View Online at <https://aerobasegroup.com/nsn/5305-00-403-2832>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.235 inches and 0.265 inches

**Fastener Length:**

Between 0.771 inches and 0.781 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.182 inches and 0.192 inches

**Head Height:**

Between 0.026 inches and 0.036 inches

**First Diameter From Head:**

Between 0.115 inches and 0.120 inches

**Second Diameter From Head:**

Between 0.073 inches and 0.078 inches

**Third Diameter From Head:**

0.112 inches

**Fourth Diameter From Head:**

Between 0.073 inches and 0.078 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

0.062 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

0.218 inches

**Distance From Largest Bearing Surface Of Head To End Of Third Diameter:**

0.468 inches

**Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:**

0.781 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.112 inches

**Thready Qty Per Inch (tpi):**

40

**Externally Relieved Body Diameter Quantity:**

4

**Special Features:**

Third diameter from head is the threaded portion

**Material Specification:**

Qq-s-633 federal specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-s-633, type 2, class 3 federal specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0