

View Online at <https://aerobasegroup.com/nsn/5305-00-403-2832>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.235 inches and 0.265 inches

Fastener Length:

Between 0.771 inches and 0.781 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.182 inches and 0.192 inches

Head Height:

Between 0.026 inches and 0.036 inches

First Diameter From Head:

Between 0.115 inches and 0.120 inches

Second Diameter From Head:

Between 0.073 inches and 0.078 inches

Third Diameter From Head:

0.112 inches

Fourth Diameter From Head:

Between 0.073 inches and 0.078 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

0.062 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

0.218 inches

Distance From Largest Bearing Surface Of Head To End Of Third Diameter:

0.468 inches

Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:

0.781 inches

Internal Drive Style:

Slot

Thread Diameter:

0.112 inches

Thready Qty Per Inch (tpi):

40

Externally Relieved Body Diameter Quantity:

4

Special Features:

Third diameter from head is the threaded portion

Material Specification:

Qq-s-633 federal specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-s-633, type 2, class 3 federal specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0