# NSN 5305-00-403-3460

Shoulder Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-403-3460

#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

### Thread Length:

Between 0.330 inches and 0.390 inches

#### Fastener Length:

2.340 inches

#### **Head Style:**

Flat chamfer

#### Head Diameter:

0.500 inches

#### Head Height:

Between 0.140 inches and 0.170 inches

#### Shoulder Diameter:

0.3750 inches first shoulder and 0.3754 inches first shoulder

#### Shoulder Length:

1.950 inches first shoulder

#### Shank Unthreaded Hole Diameter:

0.081 inches first hole

#### **Internal Drive Style:**

Slot

#### Thread Diameter:

0.250 inches

#### Thready Qty Per Inch (tpi):

28

#### Min. Tensile Strength (psi):

180000 pounds per square inch

# Distance From Head Largest Bearing Surface To Shank Hole Center:

2.168 inches first hole

## Shoulder Shape:

Round first shoulder

## Material:

Steel comp 630

# Material Specification:

Ams5643 assn standard single material response

# Surface Treatment:

Passivate

# Surface Treatment Specification:

Ess-001 fscm 81873 mfr ref single treatment response

## **Thread Series Designator:**

Unf



# NSN 5305-00-403-3460

Shoulder Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

