## NSN 5305-00-403-3497

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-403-3497

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.688 inches and 0.750 inches
Fastener Length:
Between 0.720 inches and 0.750 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.262 inches and 0.270 inches
Head Height:
Between 0.159 inches and 0.164 inches
Width Between Flats:
Between 0.141 inches and 0.143 inches
Internal Drive Style:
Err-090
Thread Diameter:
0.164 inches
Width Across Flats:
Between 0.141 inches and 0.143 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
80000 pounds per square inch
Hardness Rating:
80.0 rockwell b
Screw Material:
Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384
Screw Material Specification:
Astm a493 assn standard all material responses
Screw Surface Treatment:
Passivate
Thread Series Designator:
Unrc
Specification Data:
80205-nas1352 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5305-00-403-3497

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0