

View Online at <https://aerobasegroup.com/nsn/5305-00-403-3497>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.688 inches and 0.750 inches

**Fastener Length:**

Between 0.720 inches and 0.750 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.262 inches and 0.270 inches

**Head Height:**

Between 0.159 inches and 0.164 inches

**Width Between Flats:**

Between 0.141 inches and 0.143 inches

**Internal Drive Style:**

Err-090

**Thread Diameter:**

0.164 inches

**Width Across Flats:**

Between 0.141 inches and 0.143 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

80000 pounds per square inch

**Hardness Rating:**

80.0 rockwell b

**Screw Material:**

Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384

**Screw Material Specification:**

Astm a493 assn standard all material responses

**Screw Surface Treatment:**

Passivate

**Thread Series Designator:**

Unrc

**Specification Data:**

80205-nas1352 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0