# NSN 5305-00-403-7734

Setscrew - Page 1 of 2





### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Thread Length:

Between 0.296 inches and 0.316 inches

# Fastener Length:

Between 0.365 inches and 0.385 inches

#### **Head Style:**

Headless (setscrew)

# Locking Feature:

Pellet threads or strip threads

# **Point Style:**

Cone

# **Internal Drive Style:**

.....

# Hexagon

Thread Diameter:

0.138 inches

# Width Across Flats:

Between 0.063 inches and 0.064 inches

# Thready Qty Per Inch (tpi):

32

# Material:

Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316

# **Material Specification:**

66 federal standard all material responses

# Surface Treatment:

Passivate

# Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

# **Thread Series Designator:**

Unc

#### **Specification Or Standard:**

1 type and 2 style

# **Departure From Cited Designator:**

As mod by locking feature

Shelf Life:

N/a

Unit Of Measure:

---

# Demilitarization:

No

# NSN 5305-00-403-7734

Setscrew - Page 2 of 2

Fiig: A003b0

