

View Online at <https://aerobasegroup.com/nsn/5305-00-404-6275>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.234 inches and 0.266 inches

Fastener Length:

Between 0.796 inches and 0.828 inches

Head Style:

Knurled no. 1

Head Diameter:

Between 0.359 inches and 0.391 inches

Head Height:

Between 0.422 inches and 0.453 inches

First Diameter From Head:

Between 0.125 inches and 0.135 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.390 inches and 0.421 inches

Internal Drive Style:

Slot

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Externally Relieved Body Diameter Quantity:

1

Special Features:

Point style no. 6 0.141 in. Min, 0.172 in. Maximum lg, 85 to 95 degrees chamfered angle, 0.125 in. Min, 0.135 in. Maximum dia

Material:

Steel comp 303

Material Specification:

Astm a582 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-f-14072, finish e300 military specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.