NSN 5305-00-404-6275

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-404-6275 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.234 inches and 0.266 inches **Fastener Length:** Between 0.796 inches and 0.828 inches **Head Style:** Knurled no. 1 **Head Diameter:** Between 0.359 inches and 0.391 inches **Head Height:** Between 0.422 inches and 0.453 inches **First Diameter From Head:** Between 0.125 inches and 0.135 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.390 inches and 0.421 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Point style no. 6 0.141 in. Min, 0.172 in. Maximum Ig, 85 to 95 degrees chamfered angle, 0.125 in. Min, 0.135 in. Maximum dia Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072, finish e300 military specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a

--

Unit Of Measure:

NSN 5305-00-404-6275

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.