

View Online at <https://aerobasegroup.com/nsn/5305-00-404-6275>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.234 inches and 0.266 inches

**Fastener Length:**

Between 0.796 inches and 0.828 inches

**Head Style:**

Knurled no. 1

**Head Diameter:**

Between 0.359 inches and 0.391 inches

**Head Height:**

Between 0.422 inches and 0.453 inches

**First Diameter From Head:**

Between 0.125 inches and 0.135 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.390 inches and 0.421 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Externally Relieved Body Diameter Quantity:**

1

**Special Features:**

Point style no. 6 0.141 in. Min, 0.172 in. Maximum lg, 85 to 95 degrees chamfered angle, 0.125 in. Min, 0.135 in. Maximum dia

**Material:**

Steel comp 303

**Material Specification:**

Astm a582 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-f-14072, finish e300 military specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-f-14072 spec.