

View Online at <https://aerobasegroup.com/nsn/5305-00-404-6466>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.222 inches and 0.298 inches

Fastener Length:

0.468 inches

Head Style:

Pan

Head Diameter:

0.265 inches

Head Height:

Between 0.087 inches and 0.097 inches

First Diameter From Head:

Between 0.137 inches and 0.141 inches

Second Diameter From Head:

Between 0.079 inches and 0.081 inches

Third Diameter From Head:

Between 0.165 inches and 0.170 inches

Fourth Diameter From Head:

Between 0.090 inches and 0.095 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

0.090 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

Between 0.108 inches and 0.110 inches

Distance From Largest Bearing Surface Of Head To End Of Third Diameter:

Between 0.123 inches and 0.128 inches

Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:

Between 0.170 inches and 0.180 inches

Internal Drive Style:

Slot

Thread Diameter:

0.138 inches

Thready Qty Per Inch (tpi):

32

Externally Relieved Body Diameter Quantity:

4

Material:

Stainless steel

Material Specification:

Ams 5643, comp 17-4ph, cond h925 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

H+4-169, fscm 82577 mfr ref single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0