NSN 5305-00-405-1416

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-405-1416 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.380 inches **Fastener Length:** Between 0.719 inches and 0.750 inches **Head Style:** Fillister **Head Diameter:** Between 0.292 inches and 0.313 inches **Head Height:** Between 0.123 inches and 0.130 inches **First Diameter From Head:** Between 0.138 inches and 0.148 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.350 inches and 0.390 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Material Specification:** 66 federal standard all material responses **Surface Treatment: Passivate Surface Treatment Specification:** II-f-14072 e300 military specification 10th treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

NSN 5305-00-405-1416

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

spec.