NSN 5305-00-405-7577

Shoulder Screw - Page 1 of 2

Between 0.355 inches and 0.375 inches

Between 1.360 inches and 1.370 inches

Thread Class:

Right-hand

Thread Length:

Thread Direction:

Fastener Length:

За



View Online at https://aerobasegroup.com/nsn/5305-00-405-7577

Head Style:
Flat chamfer
Head Diameter:
Between 0.357 inches and 0.375 inches
Head Height:
Between 0.177 inches and 0.187 inches
Shoulder Diameter:
0.246 inches first shoulder and 0.248 inches first shoulder
Shoulder Length:
0.995 inches first shoulder and 1.005 inches first shoulder
Single Shear Strength:
1170 pounds per square inch
Internal Drive Style:
Hexagon
Thread Diameter:
0.190 inches
Width Across Flats:
0.125 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
140000 pounds per square inch
Shoulder Shape:
Round first shoulder
Special Features:
Self-locking nylon strip insert in threaded end
Material:
Steel
Material Specification:
Sae 4037 assn standard single material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416, type 2, class 3 federal specification single treatment response

NSN 5305-00-405-7577

Shoulder Screw - Page 2 of 2



Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0