NSN 5305-00-405-8345

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-405-8345 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.359 inches and 0.391 inches **Fastener Length:** Between 1.359 inches and 1.391 inches **Head Style:** Knurled no. 1 **Head Diameter:** Between 0.745 inches and 0.755 inches **Head Height:** Between 0.234 inches and 0.266 inches **First Diameter From Head:** Between 0.170 inches and 0.180 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.990 inches and 1.010 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 20 **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Cone point 82 deg Material: Steel comp 303 **Material Specification:** Qq-s-764 cond a federal specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072, finish e300 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-00-405-8345

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.