

View Online at <https://aerobasegroup.com/nsn/5305-00-406-0095>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.295 inches and 0.325 inches

Fastener Length:

Between 2.131 inches and 2.216 inches

Head Style:

Fillister

Head Diameter:

Between 0.715 inches and 0.785 inches

Head Height:

Between 0.186 inches and 0.206 inches

Shoulder Diameter:

0.497 inches first shoulder and 0.499 inches first shoulder

Shoulder Length:

1.630 inches first shoulder and 1.635 inches first shoulder

Internal Drive Style:

Slot

Thread Diameter:

0.312 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

190000 pounds per square inch

Minimum Yield Strength:

170000 pounds per square inch

Shoulder Shape:

Round first shoulder

Material:

Stainless steel

Material Specification:

Ams 5643 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-s-5002 military specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5002 spec.