NSN 5305-00-406-0680

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-406-0680 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.259 inches and 0.391 inches **Fastener Length:** Between 0.359 inches and 0.391 inches **Head Style:** Round **Head Diameter:** Between 0.419 inches and 0.437 inches **Head Height:** Between 0.122 inches and 0.132 inches **Locking Feature:** Pellet threads **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: 0.312 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 80000 pounds per square inch **Hardness Rating:** 80.0 rockwell b Minimum Yield Strength: 30000 pounds per square inch Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Material Specification:** 66 federal standard all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc

Shelf Life:

N/a

NSN 5305-00-406-0680

Socket Head Cap Screw - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A003b0