## NSN 5305-00-406-0683



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-406-0683 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.547 inches and 0.641 inches **Fastener Length:** Between 0.609 inches and 0.641 inches **Head Style:** Hexagon extended washer **Head Height:** Between 0.128 inches and 0.136 inches Width Between Flats: Between 0.244 inches and 0.250 inches **Extended Washer Diameter:** Between 0.358 inches and 0.380 inches **Extended Washer Thickness:** Between 0.026 inches and 0.032 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 **Screw Material:** Steel comp 303 **Screw Material Specification:** Qq-s-764 federal specification single material response **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Mil-s-5002 military specification single treatment response **Thread Series Designator:** Unc

Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig: A500d0

## NSN 5305-00-406-0683

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-5002 spec.