## NSN 5305-00-406-5394

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-406-5394 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.374 inches and 0.453 inches **Fastener Length:** Between 1.265 inches and 1.312 inches **Head Style:** Hexagon **Head Height:** Between 0.109 inches and 0.141 inches Width Between Flats: Between 0.365 inches and 0.377 inches **First Diameter From Head:** Between 0.168 inches and 0.178 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.859 inches and 0.891 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 125000 pounds per square inch **Externally Relieved Body Diameter Quantity:** Material: Steel comp 431 **Material Specification:** Mil-s-18732 military specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** 

--

## NSN 5305-00-406-5394

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-18732 spec.