## NSN 5305-00-406-8031

**Thread Class:** 

**Thread Direction:** 

За

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-406-8031

Right-hand
Thread Length:
1.000 inches
Fastener Length:
Between 1.484 inches and 1.531 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.365 inches and 0.375 inches
Head Height:
Between 0.244 inches and 0.250 inches
Locking Feature:
Pellet threads
Internal Drive Style:
Hexagon
Thread Diameter:
0.250 inches
Width Across Flats:
Between 0.187 inches and 0.190 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 45.0 rockwell c
Minimum Yield Strength:
130000 pounds per square inch
Material:
Steel fastener
Steel lasteriel
Material Specification:
Material Specification:
Material Specification: 66 federal standard single material response
Material Specification: 66 federal standard single material response Surface Treatment:
Material Specification:  66 federal standard single material response  Surface Treatment:  Cadmium fastener and chromate fastener
Material Specification: 66 federal standard single material response Surface Treatment: Cadmium fastener and chromate fastener Surface Treatment Specification:
Material Specification: 66 federal standard single material response Surface Treatment: Cadmium fastener and chromate fastener Surface Treatment Specification: Qq-p-416, type 2 class 2 federal specification single treatment response fastener

80205-nas1351 professional/industrial association standard

## NSN 5305-00-406-8031

Socket Head Cap Screw - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0