## NSN 5305-00-407-2165

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-407-2165

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.095 inches and 0.126 inches
Fastener Length:
Between 0.266 inches and 0.297 inches
Head Style:
Pan no. 2
Head Diameter:
Between 0.256 inches and 0.270 inches
Head Height:
Between 0.072 inches and 0.082 inches
First Diameter From Head:
0.101 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
0.171 inches
Internal Drive Style:
Slot
Thread Diameter:
0.138 inches
Thready Qty Per Inch (tpi):
40
Min. Tensile Strength (psi):
55000 pounds per square inch
Externally Relieved Body Diameter Quantity:
1
Material Specification:
Qq-s-634 federal specification 1st material response or qq-s-634 federal specification 2nd material response or qq-s-634 federal
specification 3rd material response or qq-s-634 federal specification 4th material response or qq-s-634 federal specification 5th material
response or qq-s-634 federal specification 6th material response or qq-s-634 federal specification 7th material response or qq-s-634
federal specification 8th material response or qq-s-634 federal specification 9th material response or qq-s-634 federal specification 10th
material response or qq-s-634 federal specification 11th material response or qq-s-634 federal specification 12th material response or
qq-s-634 federal specification 13th material response or qq-s-634-jbsqq-s-634 federal specification 14th material response or qq-s-634

federal specification 16th material response or qq-s-634 federal specification 17th material response or qq-s-630 federal specification 18th material response or qqs-631 federal specification 18th material response or qqs-631 federal specification 18th material response or qqs-637 federal specification 18th q

## **Surface Treatment:**

Cadmium

Chalf Lifa.

## **Surface Treatment Specification:**

qq-s-405 federal specification 18th material response

Qq-p-416, type 2, class 2 federal specification single treatment response

**Thread Series Designator:** 

Unf

## NSN 5305-00-407-2165

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0