

View Online at <https://aerobasegroup.com/nsn/5305-00-407-2165>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.095 inches and 0.126 inches

Fastener Length:

Between 0.266 inches and 0.297 inches

Head Style:

Pan no. 2

Head Diameter:

Between 0.256 inches and 0.270 inches

Head Height:

Between 0.072 inches and 0.082 inches

First Diameter From Head:

0.101 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

0.171 inches

Internal Drive Style:

Slot

Thread Diameter:

0.138 inches

Thready Qty Per Inch (tpi):

40

Min. Tensile Strength (psi):

55000 pounds per square inch

Externally Relieved Body Diameter Quantity:

1

Material Specification:

Qq-s-634 federal specification 1st material response or qq-s-634 federal specification 2nd material response or qq-s-634 federal specification 3rd material response or qq-s-634 federal specification 4th material response or qq-s-634 federal specification 5th material response or qq-s-634 federal specification 6th material response or qq-s-634 federal specification 7th material response or qq-s-634 federal specification 8th material response or qq-s-634 federal specification 9th material response or qq-s-634 federal specification 10th material response or qq-s-634 federal specification 11th material response or qq-s-634 federal specification 12th material response or qq-s-634 federal specification 13th material response or qq-s-634-jbsqq-s-634 federal specification 14th material response or qq-s-634 federal specification 16th material response or qq-s-634 federal specification 17th material response or qq-s-630 federal specification 18th material response or qq-s-631 federal specification 18th material response or qq-s-637 federal specification 18th material response or qq-s-405 federal specification 18th material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

Fig:

A003b0