NSN 5305-00-407-5535

Thread Class:

Right-hand

Thread Direction:

За

N/a

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-407-5535

Thread Length:
Between 0.532 inches and 0.625 inches
Fastener Length:
Between 0.594 inches and 0.625 inches
Head Style:
Pan
Head Diameter:
Between 0.256 inches and 0.270 inches
Head Height:
Between 0.087 inches and 0.097 inches
Locking Feature:
Pellet threads
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.138 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
140000 pounds per square inch
Hardness Rating:
248.0 brinell standard and 341.0 brinell standard
Surface Finish:
32.0 microinches threads
Material:
Iron alloy 660
Material Specification:
Ams 5735 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjc
Specification Data:
80205-nas1190 professional/industrial association standard
Shelf Life:

NSN 5305-00-407-5535

Socket Head Cap Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0