

View Online at <https://aerobasegroup.com/nsn/5305-00-407-5549>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.357 inches and 0.393 inches

**Fastener Length:**

Between 1.185 inches and 1.205 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.095 inches and 0.110 inches

**Width Between Flats:**

Between 0.367 inches and 0.376 inches

**Locking Feature:**

Detent ball grip or detent ring grip

**Shank Unthreaded Hole Diameter:**

0.070 inches first hole and 0.080 inches first hole

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Hardness Rating:**

50.0 rockwell c locking feature and 62.0 rockwell c locking feature

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.095 inches first hole and 1.115 inches first hole

**Surface Finish:**

32.0 microinches grip

**Material:**

Steel comp 631 spring or steel comp 302 spring

**Material Specification:**

Qq-s-763, cl fsc4000 federal specification single material response locking feature

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0