

View Online at <https://aerobasegroup.com/nsn/5305-00-407-5549>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.357 inches and 0.393 inches

Fastener Length:

Between 1.185 inches and 1.205 inches

Head Style:

Hexagon

Head Height:

Between 0.095 inches and 0.110 inches

Width Between Flats:

Between 0.367 inches and 0.376 inches

Locking Feature:

Detent ball grip or detent ring grip

Shank Unthreaded Hole Diameter:

0.070 inches first hole and 0.080 inches first hole

Internal Drive Style:

Slot

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Hardness Rating:

50.0 rockwell c locking feature and 62.0 rockwell c locking feature

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.095 inches first hole and 1.115 inches first hole

Surface Finish:

32.0 microinches grip

Material:

Steel comp 631 spring or steel comp 302 spring

Material Specification:

Qq-s-763, cl fsc4000 federal specification single material response locking feature

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0