

View Online at <https://aerobasegroup.com/nsn/5305-00-408-3479>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.080 inches

**Fastener Length:**

0.810 inches

**Head Style:**

Hexagon

**Head Height:**

0.120 inches

**Width Between Flats:**

0.250 inches

**First Diameter From Head:**

Between 0.123 inches and 0.124 inches

**Second Diameter From Head:**

Between 0.070 inches and 0.080 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

0.670 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

0.730 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.112 inches

**Thready Qty Per Inch (tpi):**

40

**Externally Relieved Body Diameter Quantity:**

2

**Material:**

Steel comp 303

**Material Specification:**

Qq-s-764 federal specification single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-f-14072, finish e300, ty1 military specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-f-14072 spec.