NSN 5305-00-410-0644

Socket Head Cap Screw - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-00-410-0644

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.309 inches and 0.375 inches |
| Fastener Length: |
| Between 0.345 inches and 0.375 inches |
| Head Style: |
| Button |
| Head Diameter: |
| Between 0.176 inches and 0.188 inches |
| Head Height: |
| Between 0.044 inches and 0.052 inches |
| Locking Feature: |
| Patch threads or pellet threads or strip threads |
| Internal Drive Style: |
| Hexagon |
| Thread Diameter: |
| 0.099 inches |
| Width Across Flats: |
| 0.0625 inches |
| Thready Qty Per Inch (tpi): |
| 56 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Hardness Rating: |
| 36.0 rockwell c and 45.0 rockwell c |
| Color: |
| Black |
| Material: |
| Steel |
| Surface Treatment: |
| Oxide |
| Thread Series Designator: |
| Unrf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

NSN 5305-00-410-0644

Socket Head Cap Screw - Page 2 of 2

Fiig: A003b0

