## NSN 5305-00-410-3389

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-410-3389 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.537 inches and 0.587 inches **Fastener Length:** Between 1.109 inches and 1.139 inches **Head Style:** Bevel-conical **Head Diameter:** Between 0.521 inches and 0.531 inches **Head Height:** 0.312 inches **Shoulder Diameter:** 0.342 inches first shoulder and 0.343 inches first shoulder **Shoulder Length:** 0.552 inches first shoulder and 0.572 inches first shoulder **Internal Drive Style:** Hexagon **Thread Diameter:** 0.312 inches Width Across Flats: Between 0.219 inches and 0.221 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** 34.0 rockwell c and 40.0 rockwell c **Shoulder Shape:** Round first shoulder Material: Steel **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416 type 2 class 3 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life:

N/a

## NSN 5305-00-410-3389

Shoulder Screw - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0