Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-410-6524

| Thread Class:  |
|--|
| 2a<br>Thread Direction:  |
|  |
| Right-hand   |
| Thread Length:   |
| Between 0.303 inches and 0.313 inches  |
| Fastener Length:   |
| 1.188 inches   |
| Head Style:  |
| Knurled no. 1  |
| Head Diameter:   |
| Between 0.495 inches and 0.505 inches  |
| Head Height:   |
| Between 0.546 inches and 0.578 inches  |
| First Diameter From Head:  |
| Between 0.170 inches and 0.180 inches  |
| Distance From Largest Bearing Surface Of Head To End Of First Diameter:        |
| Between 0.677 inches and 0.697 inches  |
| Internal Drive Style:  |
| Slot   |
| Thread Diameter:   |
| 0.250 inches   |
| Thready Qty Per Inch (tpi):  |
| 20   |
| Externally Relieved Body Diameter Quantity:                                    |
|  |
| Product Name:  |
| Navy special project   |
| Special Features:  |
| Point style no. 6, 0.188 in. Lg, 90 degrees point chamfer angle, 0.175 in. Dia |
| Material:  |
| Stainless steel  |
| Surface Treatment:   |
|  |
| Thread Series Designator:  |
| Unc  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |

## NSN 5305-00-410-6524

Externally Relieved Body Screw - Page 2 of 2

Fiig: A003b0

