

View Online at <https://aerobasegroup.com/nsn/5305-00-410-6549>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.310 inches

Fastener Length:

Between 1.450 inches and 1.470 inches

Head Style:

Fillister

Head Diameter:

Between 0.208 inches and 0.226 inches

Head Height:

Between 0.086 inches and 0.096 inches

First Diameter From Head:

Between 0.085 inches and 0.090 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

1.160 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.138 inches

Thready Qty Per Inch (tpi):

32

Externally Relieved Body Diameter Quantity:

1

Special Features:

Cone point 90 degrees of angle

Material:

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385

Material Specification:

66 federal standard all material responses

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-f-14072, finish e300 military specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.