# NSN 5305-00-410-6732

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-410-6732



#### **Thread Class:**

2a

**Thread Direction:** 

Right-hand

## Thread Length:

Between 0.657 inches and 0.750 inches

## Fastener Length:

Between 0.719 inches and 0.750 inches

## Head Style:

Pan

Head Diameter:

Between 0.306 inches and 0.322 inches

#### **Head Height:**

Between 0.105 inches and 0.115 inches

#### Internal Drive Style:

Cross recess type 1

#### Thread Diameter:

0.164 inches

#### Thready Qty Per Inch (tpi):

32

#### Min. Tensile Strength (psi):

80000 pounds per square inch

#### Screw Material:

Stainless steel or steel

#### Screw Material Specification:

Qq-s-763, 300 series federal specification 1st material response or 66, 300 series federal standard 1st material response or comp 16-18 or

18-8 assn standard 2nd material response

#### Screw Surface Treatment:

Oxide

## Screw Surface Treatment Specification:

Mil-c-13924, cl 4 military specification single treatment response

## Thread Series Designator:

Unc

## **Specification Or Standard:**

3 type and 2c style

## Shelf Life:

N/a

## Unit Of Measure:

---

#### Demilitarization:

No

# Fiig:

A500d0

NSN 5305-00-410-6732

Machine Screw - Page 2 of 2

Mil-std (military Standard):

Mil-c-13924 spec.

