Externally Relieved Body Screw - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-00-410-8184

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.074 inches and 0.085 inches
Fastener Length:
0.500 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.150 inches and 0.172 inches
First Diameter From Head:
0.086 inches
Second Diameter From Head:
Between 0.057 inches and 0.062 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
Between 0.074 inches and 0.085 inches
Distance From Largest Bearing Surface Of Head To End Of Second Diameter:
0.500 inches
Internal Drive Style:
Cross recess type ii
Thread Diameter:
0.086 inches
Thready Qty Per Inch (tpi):
56
Countersink Angle:
82.0 degrees
Externally Relieved Body Diameter Quantity:
2
Special Features:
First diameter from head is the threaded portion
Material:
Steel comp 302 or steel comp 303 or steel comp 304
Material Specification:
Qq-s-763 federal specification all material responses
Surface Treatment:
Passivate
Thread Series Designator:
Unc
Shelf Life:
N/a

Externally Relieved Body Screw - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0