

View Online at <https://aerobasegroup.com/nsn/5305-00-411-0643>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.470 inches and 0.510 inches

**Fastener Length:**

Between 0.552 inches and 0.572 inches

**Head Style:**

Double hexagon w/ hole

**Head Height:**

Between 0.220 inches and 0.240 inches

**Width Between Flats:**

Between 0.212 inches and 0.220 inches

**Extended Washer Diameter:**

Between 0.302 inches and 0.322 inches

**Extended Washer Thickness:**

Between 0.030 inches and 0.040 inches

**Hole Diameter:**

0.047 inches

**Thread Diameter:**

0.164 inches

**Hole Quantity:**

4

**Thready Qty Per Inch (tpi):**

36

**Min. Tensile Strength (psi):**

130000 pounds per square inch

**Hardness Rating:**

Between 248.0 brinell standard and 341.0 brinell standard

**Screw Material:**

Iron alloy 660

**Screw Material Specification:**

Ams 5731 assn standard single material response

**Screw Surface Treatment:**

Silver

**Screw Surface Treatment Specification:**

Ams 2410 assn standard single treatment response

**Head Hole Configuration Style:**

Round

**Precious Material:**

Silver

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0