Externally Relieved Body Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-411-0703

| Thread Class: | |
|--------------------|--|
| 3a | |
| Thread Direction: | |
| Right-hand | |
| Thread Length: | |
| 0.375 inches | |
| Fastener Length: | |
| 0.500 inches | |
| Head Style: | |
| Flat chamfer | |
| Head Diameter: | |
| Between 1.203 inc | hes and 1.219 inches |
| Head Height: | |
| Between 0.312 inc | hes and 0.328 inches |
| First Diameter Fro | om Head: |
| 0.281 inches | |
| Distance From La | rgest Bearing Surface Of Head To End Of First Diameter: |
| 0.125 inches | |
| Internal Drive Sty | le: |
| Slot | |
| Thread Diameter: | |
| 0.375 inches | |
| Thready Qty Per I | nch (tpi): |
| 16 | |
| Externally Relieve | ed Body Diameter Quantity: |
| 1 | |
| Product Name: | |
| Navy special proje | ct |
| Material: | |
| Steel comp 1005 | or steel comp 1006 or steel comp 1008 or steel comp 1009 or steel comp 1010 or steel comp 1011 |
| Material Specifica | tion: |
| Aisi assn standard | all material responses |
| Thread Series De | signator: |
| Unc | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A003b0 | |