NSN 5305-00-411-6534

Close Tolerance Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-411-6534



Thread Class: За **Thread Direction:** Right-hand Thread Length: Between 0.623 inches and 0.690 inches **Fastener Length:** Between 1.758 inches and 1.805 inches **Head Style:** Flat countersunk **Head Diameter:** Between 1.007 inches and 1.017 inches **Grip Diameter:** Between 0.4985 inches and 0.4995 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.500 inches **Grip Length:** Between 1.115 inches and 1.135 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 50.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Product Name:** Navy special project Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Macps13145 fscm 76301 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

NSN 5305-00-411-6534

Close Tolerance Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0