

View Online at <https://aerobasegroup.com/nsn/5305-00-411-6536>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.623 inches and 0.690 inches

**Fastener Length:**

Between 2.133 inches and 2.180 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 1.007 inches and 1.017 inches

**Grip Diameter:**

Between 0.4985 inches and 0.4995 inches

**Internal Drive Style:**

High-torque

**Thread Diameter:**

0.500 inches

**Grip Length:**

Between 1.490 inches and 1.510 inches

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Hardness Rating:**

46.0 rockwell c and 50.0 rockwell c

**Countersink Angle:**

Between 99.0 degrees and 110.0 degrees

**Material:**

Steel comp h11

**Material Specification:**

Ams 6487 assn standard single material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Mac ps13145 fscm 76301 mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0