NSN 5305-00-411-7723

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-411-7723

| Inread Class: |
|----------------------------------------------------------------------------------------------------------------------------------------|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.359 inches and 0.391 inches |
| Fastener Length: |
| Between 0.359 inches and 0.391 inches |
| Head Style: |
| Flat chamfer |
| Head Diameter: |
| Between 0.262 inches and 0.270 inches |
| Head Height: |
| Between 0.159 inches and 0.164 inches |
| Hole Diameter: |
| 0.047 inches |
| Internal Drive Style: |
| Hexagon |
| Thread Diameter: |
| 0.164 inches |
| Width Across Flats: |
| Between 0.141 inches and 0.143 inches |
| Hole Quantity: |
| 6 |
| Hole Type: |
| Drilled |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 80000 pounds per square inch |
| Hardness Rating: |
| 80.0 rockwell b |
| Minimum Yield Strength: |
| 30000 pounds per square inch |
| Hole Configuration Style: |
| Round internal hexagon |
| Criticality Code Justification: |
| Feat |
| Special Features: |
| Item does not have a nuclear hardened feature but does have other critical features such as tolerance, fit restrictions or application |
| Material: |

Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 or nickel alloy

NSN 5305-00-411-7723

Socket Head Cap Screw - Page 2 of 2



| Surface Treatment: |
|---------------------------------------------------------|
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator: |
| Unrc |
| Specification Or Standard: |
| 6 type |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A003b0