NSN 5305-00-411-8993

Lag Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-411-8993

1.500 inches Head Style: Hexagon Head Height: Between 0.226 inches and 0.268 inches Width Between Flats: Between 0.544 inches and 0.562 inches Shoulder Diameter: 0.360 inches first shoulder and 0.388 inches first shoulder Shoulder Length:
Hexagon Head Height: Between 0.226 inches and 0.268 inches Width Between Flats: Between 0.544 inches and 0.562 inches Shoulder Diameter: 0.360 inches first shoulder and 0.388 inches first shoulder Shoulder Length:
Head Height: Between 0.226 inches and 0.268 inches Width Between Flats: Between 0.544 inches and 0.562 inches Shoulder Diameter: 0.360 inches first shoulder and 0.388 inches first shoulder Shoulder Length:
Between 0.226 inches and 0.268 inches Width Between Flats: Between 0.544 inches and 0.562 inches Shoulder Diameter: 0.360 inches first shoulder and 0.388 inches first shoulder Shoulder Length:
Width Between Flats: Between 0.544 inches and 0.562 inches Shoulder Diameter: 0.360 inches first shoulder and 0.388 inches first shoulder Shoulder Length:
Between 0.544 inches and 0.562 inches Shoulder Diameter: 0.360 inches first shoulder and 0.388 inches first shoulder Shoulder Length:
Shoulder Diameter: 0.360 inches first shoulder and 0.388 inches first shoulder Shoulder Length:
0.360 inches first shoulder and 0.388 inches first shoulder Shoulder Length:
Shoulder Length:
0.125 inches first shoulder
Nonmachine Thread Style:
Gimlet point (type a, ab or ba)
Nonmachine Thread Diameter:
0.375 inches
Shoulder Shape:
Round first shoulder
Material:
Copper alloy 651
Material Specification:
Qq-c 591 federal specification single material response
Specification Or Standard:
1 type and 1 style and d grade
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0