NSN 5305-00-412-9753

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-412-9753 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.202 inches and 0.212 inches **Fastener Length:** Between 0.672 inches and 0.687 inches **Head Style:** Knurled no. 1 **Head Diameter:** Between 0.307 inches and 0.317 inches **Head Height:** Between 0.296 inches and 0.328 inches **First Diameter From Head:** Between 0.115 inches and 0.125 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.372 inches and 0.392 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Point style no. 6, 0.078 in. Min, 0.120 in. Maximum Ig 85 to 95 degrees chamfer angle, 0.104 in. Min, 0.120 in. Maximum dia Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

--

Unit Of Measure:

NSN 5305-00-412-9753

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0