NSN 5305-00-412-9920

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-412-9920 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.320 inches **Fastener Length:** Between 0.469 inches and 0.500 inches **Head Style:** Pan **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.087 inches and 0.097 inches **First Diameter From Head:** Between 0.090 inches and 0.100 inches **Second Diameter From Head:** Between 0.074 inches and 0.076 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.120 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.180 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 80000 pounds per square inch **Externally Relieved Body Diameter Quantity:** Material: Stainless steel or steel **Material Specification:** Qq-s-763, 300 series federal specification 1st material response or 66, 300 series federal standard 1st material response or comp 16-18 or 18-8 assn standard 2nd material response **Surface Treatment:** Oxide **Surface Treatment Specification:**

Unc

Thread Series Designator:

Mil-c-13924 cl 4 military specification single treatment response

NSN 5305-00-412-9920

Externally Relieved Body Screw - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

Mil-std (military Standard): Mil-c-13924 spec.