NSN 5305-00-413-4073

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-413-4073 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.250 inches **Fastener Length:** 0.656 inches **Head Style:** Pan **Head Diameter:** Between 0.473 inches and 0.492 inches **Head Height:** Between 0.162 inches and 0.175 inches **First Diameter From Head:** Between 0.246 inches and 0.249 inches **Second Diameter From Head:** Between 0.134 inches and 0.144 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.097 inches and 0.099 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.406 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 2 Material: Iron alloy 660 **Material Specification:** Ams 5732 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life:

N/a

NSN 5305-00-413-4073

Externally Relieved Body Screw - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0