## NSN 5305-00-413-6434



Socket Head Cap Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-413-6434 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.412 inches and 0.478 inches **Fastener Length:** Between 0.547 inches and 0.593 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.283 inches and 0.332 inches **Locking Feature:** Patch threads or pellet threads or strip threads **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 80000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp 302 or steel comp 430 or steel comp 431 **Material Specification:** Qq-s-763 cl a federal specification 1st material response or qq-s-763 cl a federal specification 2nd material response or mil-s-18732 military specification 3rd material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

Fiig:

No

A003b0

**Demilitarization:** 

## NSN 5305-00-413-6434

Socket Head Cap Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-18732 spec.