## NSN 5305-00-413-9568

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-413-9568 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.200 inches **Fastener Length:** Between 0.845 inches and 0.865 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.213 inches and 0.218 inches **Head Height:** Between 0.115 inches and 0.135 inches **First Diameter From Head:** Between 0.138 inches and 0.140 inches **Second Diameter From Head:** Between 0.093 inches and 0.098 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.126 inches and 0.131 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.645 inches and 0.665 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 2 Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072, finish e300 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

## NSN 5305-00-413-9568

Externally Relieved Body Screw - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.